

EL 160 E2M 01


121746

- Innovative, high-efficiency diagonal fan
- Optimally tuned, CFD-optimized aerodynamics
- The benchmark for efficiency since 2007
- Robust AC motor, 3-steps controllable
- Conveyed medium temperature up to 80 °C in continuous operation
- Housing made of polyamide



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxHduct
Pipe connection size (DN)	DN160		DN
Rated voltage (entire device)	230	v	U _{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Plastic		matcasing
Impeller material	Plastic		matimpeller
IP-protection class (entire device)	IPX4		IPcompl
Weight	2.2	kg	m
Fan type	Diagonal		Fan _{type}
Category / Installation situation	A		cat

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	53	w	P _{ed, max}
Max. operating current (device)	0.33	A	I _{ed, max}
Max. speed	2840	rpm	n _{max}
Max. stat. efficiency	31.6	p	η _{es}
Max. fan efficiency	32.9	p	η _e
Max. flowrate	470	CmH	Q _{v, max}
Max. stat pressure	290	Pa	p _{sf, max}
Max. medium temperature	80	°C	T _{m, max}
Max. environment temperature	80	°C	T _{amb, max}
Min. environment temperature	-25	°C	T _{amb, min}
Min. voltage	230	v	U _{min}
Stall current	0.86	A	I _{LRA}



MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 1~		phase
Control type		step-controlled		ctrltype
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TAI		protectmotor
Protection class		IP00		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwrsupmotor
Capacity capacitor		1.5	μF	Ccond
Voltage capacitor		450	v	VUcond
Number of poles (1)		2.000000		num polesw1
Rated voltage	230		v	Urated, f1
Rated current	0.3		A	Irated, f1
UL-Certification motor		None		ULcert

ERP DATA (LOT11)

Name	Value	Unit	Formula symbol
Speed at the energy efficiency optimum	2701	rpm	n _{opt}
Efficiency level	31.8	p	N
Efficiency category	statisch		catefficiency
Input power of the motor at the energy efficiency optimum	0.05	kw	P _{e, opt}
Overall efficiency	55.8	p	η _{ges}
Measurement category	A		meas cat
Fan pressure at energy efficiency optimum	220	Pa	p _{f, opt}
Flowrate at energy efficiency optimum	288	CmH	Q _{v, opt}


SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Fire resistance class	None		Fclass



to the product detail page


CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS




EL 160 E2M 01

121746

ruck






EL 160 E2M 01


121746

ruck



EL 160 E2M 01

121746



to the product detail page