

EL 315 E2 10


130320

- Innovative, high-efficiency diagonal fan
- Optimally tuned, CFD-optimized aerodynamics
- The benchmark for efficiency since 2007
- Robust single phase AC motor
- Conveyed medium temperature up to 60 °C in continuous operation
- Housing made of galvanized steel sheet
- Externally ventilated motor



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxH _{duct}
Pipe connection size (DN)	DN315		DN
Rated voltage (entire device)	230	v	U _{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Galvanized steel		mat _{casing}
Impeller material	Plastic		mat _{impeller}
IP-protection class (entire device)	IPX4		IP _{compl}
IP-Protection class (terminal box)	IP44		IP _{ebox}
Weight	15	kg	m
Fan type	Diagonal		Fan _{type}
Category / Installation situation	A		cat

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	511	w	P _{ed, max}
Max. operating current (device)	3.07	A	I _{ed, max}
Max. speed	2860	rpm	n _{max}
Max. stat. efficiency	44.9	p	η _{es}
Max. fan efficiency	49.3	p	η _e
Max. flowrate	3360	CmH	Q _{v, max}
Max. stat pressure	720	Pa	p _{sf, max}
Max. medium temperature	80	°C	T _{m, max}
Max. environment temperature	60	°C	T _{amb, max}
Min. environment temperature	-25	°C	T _{amb, min}
Min. voltage	80	v	U _{min}
Stall current	8.5	A	I _{LRA}



MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 1~		phase
Control type		stepless-controlled		ctrltype
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TMI		protectmotor
Protection class		IP54		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwrsupmotor
Capacity capacitor		10	µF	Ccond
Voltage capacitor		400	v	VUcond
Number of poles (1)		2.000000		num polesw1
Rated voltage	230		v	Urated, f1
Rated current	1.9		A	Irated, f1
Nominal power	300		w	Pa
Speed	2820		rpm	n _{f1}
Cos Phi	0.990000	0.000000		cos φ
UL-Certification motor		None		ULcert

ERP DATA (LOT11)


Name	Value	Unit	Formula symbol
Speed at the energy efficiency optimum	2781	rpm	n _{opt}
Efficiency level	45.2	p	N
Efficiency category	statisch		catefficiency
Input power of the motor at the energy efficiency optimum	0.47	kw	P _{e, opt}
Overall efficiency	59.2	p	η _{ges}
Measurement category	A		meas cat
Fan pressure at energy efficiency optimum	389	Pa	p _{f, opt}
Flowrate at energy efficiency optimum	2076	CmH	q _{v, opt}

SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Fire resistance class	None		Fclass



CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS




130320 00



EL 315 E2 10

130320

ruck




130320 00



EL 315 E2 10


130320

ruck



EL 315 E2 10

130320




to the product detail page

EL 315 E2 10

130320

ruck



to the product detail page