


EM 100L E2 01


137668

- Innovative, high-efficiency diagonal fan
- Optimally tuned, CFD-optimized aerodynamics
- Housing made of impact-resistant, reinforced polypropylene
- Robust single phase AC motor
- Conveyed medium temperature up to 60 °C in continuous operation
- The benchmark for efficiency since 2012



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		$W \times H_{duct}$
Pipe connection size (DN)	DN100		DN
Rated voltage (entire device)	230	V	U_{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Plastic		matcasing
Impeller material	Plastic		matimpeller
IP-protection class (entire device)	IPX2		IPcompl
Weight	0.97	kg	m
Fan type	Diagonal		Fan _{type}
Category / Installation situation	A		cat

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	13	W	$P_{ed, max}$
Max. operating current (device)	0.21	A	$I_{ed, max}$
Max. speed	2570	1/min	n_{max}
Max. stat. efficiency	6.5	%	η_{es}
Max. fan efficiency	7.4	%	η_e
Max. flowrate	124	m ³ /h	$Q_{v, max}$
Max. stat pressure	80	Pa	$p_{sf, max}$
Max. medium temperature	60	°C	$T_{m, max}$
Max. environment temperature	60	°C	$T_{amb, max}$
Min. environment temperature	-25	°C	$T_{amb, min}$
Min. voltage	207	V	U_{min}



MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		Split pole		phase
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Protection class		IP00		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwsupmotor
Rated voltage	230		V	U _{rated, f1}
Rated current	0.09		A	I _{rated, f1}
Nominal power	13		W	P _a
Speed	2800		1/min	n _{f1}
UL-Certification motor		None		ULcert

ERP DATA (LOT11)


Name	Value	Unit	Formula symbol
Speed at the energy efficiency optimum	2498	1/min	n _{opt}
Efficiency level	7.4	%	N
Efficiency category	statisch		catefficiency
Input power of the motor at the energy efficiency optimum	0.01	kW	P _{e, opt}
Overall efficiency	37.7	%	η _{ges}
Measurement category	A		meas cat
Fan pressure at energy efficiency optimum	43	Pa	p _{f, opt}
Flowrate at energy efficiency optimum	87	m³/h	q _{v, opt}

SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Fire resistance class	None		Fclass




CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



EM 100L E2 01

137668

ruck




137668 00



to the product detail page

EM 100L E2 01


137668



to the product detail page

EM 100L E2 01

137668




to the product detail page

EM 100L E2 01

137668

ruck



[to the product detail page](#)