


EM 100L EC 02


145801

- Innovative, high-efficiency diagonal fan
- Optimally tuned, CFD-optimized aerodynamics
- Housing made of impact-resistant, reinforced polypropylene
- High efficiency IE5 EC motor, steplessly controllable
- External PWM control required to operate the fan (e.g. MTP50)
- Conveyed medium temperature up to 40 °C in continuous operation
- The benchmark for efficiency since 2012



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

EM 100L EC 02

145801

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxHduct
Pipe connection size (DN)	DN100		DN
Rated voltage (entire device)	230	v	U _{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Plastic		matcasing
Impeller material	Plastic		matimpeller
IP-protection class (entire device)	IPX2		IPcompl
Weight	0.84	kg	m
Fan type	Diagonal		Fan _{type}
Category / Installation situation	A		cat

MAXIMAL DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Max. power consumption (device)	12	12	w	P _{ed, max}
Max. operating current (device)	0.23	0.23	A	I _{ed, max}
Max. speed	3650	3650	rpm	n _{max}
Max. stat. efficiency	26.2	26.2	p	η _{es}
Max. fan efficiency	28.7	28.7	p	η _e
Max. flowrate	195	195	CmH	q _{v, max}
Max. stat pressure	155	155	Pa	p _{sf, max}
Max. medium temperature	40	40	°C	T _{m, max}
Max. environment temperature	40	40	°C	T _{amb, max}


[to the product detail page](#)

EM 100L EC 02

145801



MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		EC		phase
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TAI		protectmotor
Protection class		IP00		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwrsupmotor
Number of poles (1)		2.000000		num polesw1
Rated voltage	230		v	Urated, f1
Nominal power	10		w	Pa
Speed	3800		rpm	nr1
Efficiency	38		p	ηm, f1
UL-Certification motor		None		ULcert

ERP DATA (LOT11)

Name	Value	Unit	Formula symbol
Speed at the energy efficiency optimum	3638	rpm	n _{opt}
Efficiency level	32.6	p	N
Efficiency category	statisch		cat _{efficiency}
Input power of the motor at the energy efficiency optimum	0.01	kw	P _{e, opt}
Overall efficiency	64.6	p	η _{ges}
Measurement category	A		meas cat
Fan pressure at energy efficiency optimum	88	Pa	p _{f, opt}
Flowrate at energy efficiency optimum	109	CmH	q _{v, opt}


SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Fire resistance class	None		F _{class}



to the product detail page


CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



EM 100L EC 02

145801

ruck




145801 00



to the product detail page

EM 100L EC 02

145801




to the product detail page

EM 100L EC 02

145801

ruck




to the product detail page

EM 100L EC 02

145801

ruck



to the product detail page