


EM 125L E2 01


137670

- Innovative, high-efficiency diagonal fan
- Optimally tuned, CFD-optimized aerodynamics
- Housing made of impact-resistant, reinforced polypropylene
- Robust single phase AC motor
- Conveyed medium temperature up to 40 °C in continuous operation
- The benchmark for efficiency since 2012



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		$W \times H_{duct}$
Pipe connection size (DN)	DN125		DN
Rated voltage (entire device)	230	V	U_{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Plastic		mat_{casing}
Impeller material	Plastic		$mat_{impeller}$
IP-protection class (entire device)	IPX2		IP_{compl}
Weight	1.34	kg	m
Fan type	Diagonal		Fan_{type}
Category / Installation situation	A		cat

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	31	W	$P_{ed, max}$
Max. operating current (device)	0.29	A	$I_{ed, max}$
Max. speed	2500	1/min	n_{max}
Max. stat. efficiency	9.4	%	η_{es}
Max. fan efficiency	10	%	η_e
Max. flowrate	275	m ³ /h	$Q_{v, max}$
Max. stat pressure	120	Pa	$p_{sf, max}$
Max. medium temperature	40	°C	T_m, max
Max. environment temperature	40	°C	$T_{amb, max}$
Min. environment temperature	-25	°C	$T_{amb, min}$

[to the product detail page](#)

MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		Split pole		phase
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Protection class		IP00		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwsupmotor
Rated voltage	230		V	U _{rated, f1}
Rated current	0.18		A	I _{rated, f1}
Nominal power	24		W	P _a
Speed	2800		1/min	n _{f1}
UL-Certification motor		None		ULcert

ERP DATA (LOT11)


Name	Value	Unit	Formula symbol
Speed at the energy efficiency optimum	2364	1/min	n _{opt}
Efficiency level	10.9	%	N
Efficiency category	statisch		catefficiency
Input power of the motor at the energy efficiency optimum	0.03	kW	P _{e, opt}
Overall efficiency	37.4	%	η _{ges}
Measurement category	A		meas cat
Fan pressure at energy efficiency optimum	63	Pa	p _{f, opt}
Flowrate at energy efficiency optimum	197	m³/h	q _{v, opt}

SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Fire resistance class	None		Fclass




CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



EM 125L E2 01

137670

ruck




137670 00



to the product detail page

EM 125L E2 01


137670



to the product detail page

EM 125L E2 01


137670



to the product detail page

EM 125L E2 01

137670



to the product detail page