

EM 150L E2M 01


126547

- Innovative, high-efficiency diagonal fan
- Optimally tuned, CFD-optimized aerodynamics
- Housing made of impact-resistant, reinforced polypropylene
- Robust AC motor, 3-steps controllable
- Conveyed medium temperature up to 60 °C in continuous operation
- The benchmark for efficiency since 2012



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

EM 150L E2M 01

126547

ruck

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxH _{duct}
Pipe connection size (DN)	DN150		DN
Rated voltage (entire device)	230	v	U _{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Plastic		mat _{casing}
Impeller material	Plastic		mat _{impeller}
IP-protection class (entire device)	IPX4		IP _{compl}
IP-Protection class (terminal box)	IP44		IP _{ebox}
Weight	2.47	kg	m
Fan type	Diagonal		Fan _{type}
Category / Installation situation	A		cat

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	46	w	P _{ed, max}
Max. operating current (device)	0.29	A	I _{ed, max}
Max. speed	2830	rpm	n _{max}
Max. stat. efficiency	31	p	η _{es}
Max. fan efficiency	36.6	p	η _e
Max. flowrate	600	CmH	q _{v, max}
Max. stat pressure	240	Pa	p _{sf, max}
Max. medium temperature	60	°C	T _{m, max}
Max. environment temperature	60	°C	T _{amb, max}
Min. environment temperature	-25	°C	T _{amb, min}
Min. voltage	230	v	U _{min}
Stall current	0.44	A	I _{LRA}



to the product detail page

EM 150L E2M 01

126547

ruck

MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 1~		phase
Control type		step-controlled		ctrltype
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TAI		protectmotor
Protection class		IP00		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwrsupmotor
Capacity capacitor		1.5	µF	Ccond
Voltage capacitor		450	v	VUcond
Number of poles (1)		2.000000		num polesw1
Rated voltage	230		v	Urated, f1
Rated current	0.22		A	Irated, f1
Nominal power	25		w	Pa
UL-Certification motor		None		ULcert

ERP DATA (LOT11)

Name	Value	Unit	Formula symbol
Speed at the energy efficiency optimum	2740	rpm	n _{opt}
Efficiency level	32.1	p	N
Efficiency category	statisch		cat _{efficiency}
Input power of the motor at the energy efficiency optimum	0.05	kw	P _{e, opt}
Overall efficiency	56.7	p	η _{ges}
Measurement category	A		meas cat
Fan pressure at energy efficiency optimum	143	Pa	p _{f, opt}
Flowrate at energy efficiency optimum	388	CmH	q _{v, opt}


SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Fire resistance class	None		Fclass



to the product detail page

CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS




126547 02



EM 150L E2M 01

126547




to the product detail page

EM 150L E2M 01

126547

ruck




126547 02



to the product detail page

EM 150L E2M 01
126547




to the product detail page

EM 150L E2M 01

126547

ruck



[to the product detail page](#)