

EM 200 EC 01


130561

- Innovative, high-efficiency diagonal fan
- Optimally tuned, CFD-optimized aerodynamics
- Housing made of impact-resistant, reinforced polypropylene
- High efficiency IE5 EC motor, steplessly controllable
- Incl. 1x potentiometer for connection in terminal box
- Conveyed medium temperature up to 45 °C in continuous operation
- The benchmark for efficiency since 2012



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxH _{duct}
Pipe connection size (DN)	DN200		DN
Rated voltage (entire device)	230	v	U _{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Plastic		mat _{casing}
Impeller material	Plastic		mat _{impeller}
IP-protection class (entire device)	IPX4		IP _{compl}
IP-Protection class (terminal box)	IP44		IP _{ebox}
Weight	3.31	kg	m
Fan type	Diagonal		Fan _{type}
Category / Installation situation	B		cat

MAXIMAL DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Max. power consumption (device)	116	116	w	P _{ed, max}
Max. operating current (device)	0.97	0.97	A	I _{ed, max}
Max. speed	3180	3180	rpm	n _{max}
Max. stat. efficiency	47.8	47.8	p	η _{es}
Max. fan efficiency	53.4	53.4	p	η _e
Max. flowrate	1320	1320	CmH	q _{v, max}
Max. stat pressure	450	450	Pa	p _{sf, max}
Max. medium temperature	45	45	°C	T _{m, max}
Max. environment temperature	45	45	°C	T _{amb, max}
Min. environment temperature	-30	-30	°C	T _{amb, min}


[to the product detail page](#)

EM 200 EC 01

130561

ruck

MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		EC		phase
Control type		stepless-controlled		ctrltype
Installation type		ORM (Out)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TEC		protectmotor
Protection class		IP54		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwrsupmotor
Rated voltage	230	230	v	U _{rated, f1}
Rated current	0.93	0.93	A	I _{rated, f1}
Nominal power	121	121	w	P _a
Speed	2929	2929	rpm	n _{f1}
Min. temperature	-30	-30	°C	T _{motor, min}
UL-Certification motor		None		ULcert

ERP DATA (LOT11)

Name	Value	Unit	Formula symbol
Speed at the energy efficiency optimum	2817	rpm	n _{opt}
Efficiency level	61.4	p	N
Efficiency category	total		catefficiency
Input power of the motor at the energy efficiency optimum	0.12	kw	P _{e, opt}
Overall efficiency	81.5	p	η _{ges}
Measurement category	B		meas cat
Fan pressure at energy efficiency optimum	273	Pa	p _{f, opt}
Flowrate at energy efficiency optimum	849	CmH	q _{v, opt}


SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Fire resistance class	None		Fclass



to the product detail page

CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS




130561 02



to the product detail page

EM 200 EC 01

130561




130561 02



to the product detail page

EM 200 EC 01


130561



to the product detail page

EM 200 EC 01


130561



to the product detail page

EM 200 EC 01

130561



to the product detail page