

EM 355 EC 01


130712

- Innovative, high-efficiency diagonal fan
- Optimally tuned, CFD-optimized aerodynamics
- Housing made of impact-resistant, reinforced polypropylene
- High efficiency IE5 EC motor, steplessly controllable
- Incl. 1x potentiometer for connection in terminal box
- Conveyed medium temperature up to 35 °C in continuous operation
- The benchmark for efficiency since 2012



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		$W \times H_{duct}$
Pipe connection size (DN)	DN355		DN
Rated voltage (entire device)	230	V	U_{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Plastic		mat_{casing}
Impeller material	Plastic		$mat_{impeller}$
IP-protection class (entire device)	IPX4		IP_{compl}
IP-Protection class (terminal box)	IP44		IP_{ebox}
Weight	8.7	kg	m
Fan type	Diagonal		Fan_{type}
Category / Installation situation	A		cat

MAXIMAL DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Max. power consumption (device)	261	261	W	$P_{ed, max}$
Max. operating current (device)	1.82	1.82	A	$I_{ed, max}$
Max. speed	2170	2170	1/min	n_{max}
Max. stat. efficiency	53.3	53.3	%	η_{es}
Max. fan efficiency	56.5	56.5	%	η_e
Max. flowrate	3320	3320	m³/h	Q_v, max
Max. stat pressure	450	450	Pa	$p_{sf, max}$
Max. medium temperature	35	35	°C	T_m, max
Max. environment temperature	35	35	°C	$T_{amb, max}$
Min. environment temperature	-30	-30	°C	$T_{amb, min}$



to the product detail page

MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		EC		phase
Control type		stepless-controlled		ctrltype
Installation type		ORM (Out)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TEC		protectmotor
Protection class		IP30		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwrsupmotor
Rated voltage	230	230	V	U _{rated, f1}
Rated current	1.61	1.61	A	I _{rated, f1}
Shaft power	253	253	W	P _{out, f1}
Speed	1946	1946	1/min	n _{f1}
Min. temperature	-30	-30	°C	T _{motor, min}
UL-Certification motor		None		ULcert

ERP DATA (LOT11)

Name	Value	Unit	Formula symbol
Speed at the energy efficiency optimum	1852	1/min	n _{opt}
Efficiency level	60.9	%	N
Efficiency category	statisch		catefficiency
Input power of the motor at the energy efficiency optimum	0.26	kW	P _{e, opt}
Overall efficiency	77.5	%	η _{ges}
Measurement category	A		meas cat
Fan pressure at energy efficiency optimum	278	Pa	p _{f, opt}
Flowrate at energy efficiency optimum	1839	m³/h	Q _{v, opt}


SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Fire resistance class	None		Fclass



to the product detail page


CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



EM 355 EC 01

130712

ruck



130712 02




to the product detail page

EM 355 EC 01

130712


ruck




EM 355 EC 01

130712


ruck






MECHANICAL ACCESSORIES

FV 355 | 112835



- Air filter box with mat filter ISO Coarse 45 % (G3)
- Toggle-type fastener

FT 355 | 112847



- Air filter box for pocket filter
- Toggle-type fastener
- Galvanized steel sheet housing
- Without filter

FTW 355 | 112856



- Air filter box with pocket filter M5
- Integrated warm water heating coil
- Galvanized steel sheet housing
- Toggle-type fastener

RSK 355 | 102665



- Back draught shutter for tube fitting
- Galvanized steel sheet housing
- Aluminum flaps

RSK 355D | 113491




- Back draught shutter for tube fitting
- Galvanized steel sheet housing
- Aluminum flaps
- Integrated gasket

VM 355 | 102653



- Fast clamps for sound decoupling and sealing
- Galvanized steel sheet, 5 mm Neopren gasket
- 1 Pack = 2 pieces

SG 355 01 | 169706



- Protection grille for tube connection
- Galvanized wire

SDS 355 | 169611



- Rigid tube silencer
- Galvanized steel sheet
- Sound insulation packing 50 mm (mineral wool)

SDF 355 | 169646



- Flexible tube silencer
- Galvanized steel sheet
- Sound insulation packing 50 mm



ELECTRICAL ACCESSORIES

GS 03 | 107633



- Device switch
- $U_{max} = 400 \text{ V}$, $I_{max} = 25 \text{ A}$
- Switching capacity $400 \text{ V } 3\sim = 7,5 \text{ kW}$
- Protection class IP 55

MTP 20 | 128146



- Potentiometer $10 \text{ k}\Omega$
- Switching contact $1\text{A}/250\text{V AC}$ - $2,5\text{A}/12\text{V DC}$
- Max. ambient temperature $50 \text{ }^\circ\text{C}$
- VDE

MTP 30 | 143289



- Stepped potentiometer $10 \text{ k}\Omega$
- Step 1 + 2 settable $10\% - 100\% \text{ Vdc}$
- Step 3 $100\% \text{ Vdc}$
- Supply voltage $+10 \text{ Vdc}$

SEN AIR | 148641



- Airflow and temperature transducer
- Measuring range temperature $0...+50 \text{ }^\circ\text{C}$
- With adjustable switching threshold (air speed)
- Measuring range air velocity up to 20 m/s

CON P1000 | 115259



- Constant pressure control
- Actual value display possible via optional control unit
- Output $0-10 \text{ V DC}$ + FC enable + setpoint reached
- Pressure setting by means of decade switch

MTP 50 | 168752



- Potentiometer with multifunction output
- $230 \text{ VAC} \pm 10\%$ / $50-60 \text{ Hz}$
- Selectable output: $1-10 \text{ VDC}$ / $2-20 \text{ mA}$ / $10-100\% \text{ PWM}$
- Min. and max. output value adjustable



to the product detail page