


EM 400 E4M 01


129165

- Innovative, high-efficiency diagonal fan
- Optimally tuned, CFD-optimized aerodynamics
- Housing made of impact-resistant, reinforced polypropylene
- Robust AC motor, 3-steps controllable
- Conveyed medium temperature up to 60 °C in continuous operation
- The benchmark for efficiency since 2012



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

EM 400 E4M 01

129165

ruck

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxH _{duct}
Pipe connection size (DN)	DN400		DN
Rated voltage (entire device)	230	v	U _{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Plastic		mat _{casing}
Impeller material	Plastic		mat _{impeller}
IP-protection class (entire device)	IPX4		IP _{compl}
IP-Protection class (terminal box)	IP44		IP _{ebox}
Weight	15.7	kg	m
Fan type	Diagonal		Fan _{type}
Category / Installation situation	A		cat

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	211	w	P _{ed, max}
Max. operating current (device)	1	A	I _{ed, max}
Max. speed	1440	rpm	n _{max}
Max. stat. efficiency	47.2	p	η _{es}
Max. fan efficiency	51	p	η _e
Max. flowrate	3300	CmH	q _{v, max}
Max. stat pressure	270	Pa	p _{sf, max}
Max. medium temperature	60	°C	T _{m, max}
Max. environment temperature	60	°C	T _{amb, max}
Min. environment temperature	-25	°C	T _{amb, min}
Min. voltage	230	v	U _{min}



MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 1~		phase
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TAI		protectmotor
Protection class		IP00		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwrsupmotor
Capacity capacitor		7	µF	Ccond
Voltage capacitor		450	v	VUcond
Number of poles (1)		4.000000		num polesw1
Rated voltage	230		v	Urated, f1
Rated current	1.05		A	Irated, f1
Nominal power	120		w	Pa
UL-Certification motor		None		ULcert

ERP DATA (LOT11)

Name	Value	Unit	Formula symbol
Speed at the energy efficiency optimum	1414	rpm	nopt
Efficiency level	47.5	p	N
Efficiency category	statisch		catefficiency
Input power of the motor at the energy efficiency optimum	0.21	kw	Pe, opt
Overall efficiency	65.2	p	ηges
Measurement category	A		meas cat
Fan pressure at energy efficiency optimum	178	Pa	pt, opt
Flowrate at energy efficiency optimum	2118	CmH	Qv, opt

SMOKE EXTRACT DATA


Name	Value	Unit	Formula symbol
Fire resistance class	None		Fclass



EM 400 E4M 01

129165

CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



129165 02




to the product detail page

EM 400 E4M 01

129165

ruck




129165 02




EM 400 E4M 01

129165



EM 400 E4M 01

129165




to the product detail page



EM 400 E4M 01

129165



to the product detail page