

MPS 315 D2 40


156626

- Backward curved centrifugal impeller
- Swing out fan unit
- Sheet steel housing double-walled, 40 mm mineral wool
- IE3 motor outside the airflow, frequency controllable
- Conveyed medium temperature up to 120 °C in continuous operation
- With condensate and grease drain



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

MPS 315 D2 40

156626

ruck

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxHduct
Pipe connection size (DN)	DN355		DN
Rated voltage (entire device)	400	v	U _{rated}
Phases (entire device)	3~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Galvanized steel		matcasing
Impeller material	Coated steel		matimpeller
Weight	52.9	kg	m
Nominal air flow rate, nominal point m³/h	2775.6	CmH	q _{v,nom}
Nominal external pressure, static	961.6	Pa	p _{s,nom}
Fan type	Radial		Fan _{type}
Category / Installation situation	A		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m³/s	0.77	CmS	q _{v,nom}
Actual electrical input power, nominal point	1.21	kw	P _{e,nom}
Face velocity, nominal point	7.8	mps	v _{nom}
Nominal external pressure, static	961.6	Pa	p _{s,nom}
supply air fan static efficiency, nominal point	61.5	p	η _{es,SUP}
Highest external air leakage rate	0.06	p	
Enclosure sound level, nominal point	75	db	LWA2
Rating	Product is compliant 2018		

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	1221	w	P _{ed, max}
Max. operating current (device)	2.42	A	I _{ed, max}
Max. speed	2950	rpm	n _{max}
Max. stat. efficiency	57.8	p	η _{es}
Max. fan efficiency	60.2	p	η _e
Max. flowrate	4520	CmH	q _{v, max}
Max. stat pressure	1300	Pa	p _{sf, max}
Max. medium temperature	120	°C	T _{m, max}
Max. environment temperature	60	°C	T _{amb, max}
Min. environment temperature	-20	°C	T _{amb, min}



to the product detail page

MPS 315 D2 40

156626

ruck

MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 3~		phase
Control type		frequency-controlled		ctrltype
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Protection class		IP55		IP _{motor}
Is pole-changeable		No		polexch
Type of power supply		AC 3~		pwr _{sup} motor
Number of poles (1)		2.000000		num poles _{w1}
Connection	Δ	Δ		wiring _{w1}
Connection (wiring 2)	Y	Y		wiring _{w2}
Rated voltage	230	265	v	U _{rated, f1}
Rated voltage (wiring 2)	400	460	v	U _{rated, f2}
Rated current	3.9	3.8	A	I _{rated, f1}
Rated current (wiring 2)	2.3	2.2	A	I _{rated, f2}
Nominal power	1100	1100	w	P _a
Nominal power (wiring 2)	1100	1100	w	P _{out, f2}
Speed	2890	3510	rpm	n _{r1}
Speed (wiring 2)	2890	3510	rpm	n _{r2}
Efficiency	82.7	84	p	η _{m, f1}
Efficiency (wiring 2)	82.7	84	p	η _{m, f2}
Efficiency class	IE3	IE3		IE _{motor}
Min. temperature	-30	-30	°C	T _{motor, min}
Cos Phi	0.850000	0.790000		cos φ
UL-Certification motor		None		UL _{cert}

SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Fire resistance class	None		F _{class}




to the product detail page

MPS 315 D2 40

156626


CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



to the product detail page

MPS 315 D2 40

156626







to the product detail page

MPS 315 D2 40

156626



ruck



to the product detail page

MPS 315 D2 40

156626



to the product detail page

MPS 315 D2 40

156626



to the product detail page