

MPS 500 D4 F4 30


145876

- Backward curved centrifugal impeller
- Swing out fan unit
- Sheet steel housing double-walled, 40 mm mineral wool
- IE3 motor outside the airflow, frequency controllable
- Smoke extract fan F400, 200 °C continuous operation
- With condensate and grease drain



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

MPS 500 D4 F4 30

145876

ruck

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxHduct
Pipe connection size (DN)	DN400		DN
Rated voltage (entire device)	400	v	U _{rated}
Phases (entire device)	3~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Galvanized steel		matcasing
Impeller material	Coated steel		matimpeller
Weight	112.7	kg	m
Nominal air flow rate, nominal point m³/h	5929.2	CmH	q _{v,nom}
Nominal external pressure, static	428	Pa	p _{s,nom}
Fan type	Radial		Fan _{type}
Category / Installation situation	A		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m³/s	1.65	CmS	q _{v,nom}
Actual electrical input power, nominal point	1.5	kw	P _{e,nom}
Face velocity, nominal point	13.1	mps	v _{nom}
Nominal external pressure, static	428	Pa	p _{s,nom}
supply air fan static efficiency, nominal point	59.2	p	η _{es,SUP}
Highest external air leakage rate	0.02	p	
Enclosure sound level, nominal point	77	db	LWA2
Rating	Product is compliant 2018		

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	1504	w	P _{ed, max}
Max. operating current (device)	2.98	A	I _{ed, max}
Max. speed	1490	rpm	n _{max}
Max. stat. efficiency	53.7	p	η _{es}
Max. fan efficiency	57.8	p	η _e
Max. flowrate	7890	CmH	q _{v, max}
Max. stat pressure	855	Pa	p _{sf, max}
Max. medium temperature	200	°C	T _{m, max}
Max. environment temperature	50	°C	T _{amb, max}
Min. environment temperature	-20	°C	T _{amb, min}



to the product detail page

MPS 500 D4 F4 30

145876

ruck

MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 3~		phase
Control type		frequency-controlled		ctrltype
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Protection class		IP55		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 3~		pwrsupmotor
Number of poles (1)		4.000000		num polesw1
Connection	Δ			wiringw1
Connection (wiring 2)	Y			wiringw2
Rated voltage	230		v	Urated, f1
Rated voltage (wiring 2)	400		v	Urated, f2
Rated current	4.23		A	Irated, f1
Rated current (wiring 2)	2.45		A	Irated, f2
Nominal power	1100		w	Pa
Nominal power (wiring 2)	1100		w	Pout, f2
Speed	1450		rpm	n1
Speed (wiring 2)	1450		rpm	n12
Starting current	7.6		A	Istart, f1
Starting current (wiring 2)	7.6		A	Istart, f2
Efficiency class	IE3			IEmotor
Min. temperature	-20		°C	Tmotor, min
UL-Certification motor		UL recognized		ULcert

SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Maximum resistance temperature	400	°C	Tfire
Maximum resistance time	120.000000		tfire
Fire resistance class	F 400 (120)		Fclass
Snow load class	-		SLclass




to the product detail page

MPS 500 D4 F4 30


145876

CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



MPS 500 D4 F4 30

145876




145876 00



to the product detail page

MPS 500 D4 F4 30



145876



to the product detail page

MPS 500 D4 F4 30

145876



to the product detail page

MPS 500 D4 F4 30

145876



[to the product detail page](#)