

ELKI 6035 E2 10


127736

- Energy efficient diagonal fan
- Optimally tuned and CFD-optimized aerodynamics
- Soundproof housing made of galvanized sheet steel
- Removable fan unit
- Robust single phase AC motor, voltage controllable
- Integrated thermal switch



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

ELKI 6035 E2 10

127736

ruck

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	600x350		WxH _{duct}
Pipe connection size (DN)	-		DN
Rated voltage (entire device)	230	v	U _{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Galvanized steel		mat _{casing}
Impeller material	Plastic		mat _{impeller}
IP-protection class (entire device)	IPX4		IP _{compl}
IP-Protection class (terminal box)	IP44		IP _{ebox}
Weight	25.5	kg	m
Nominal air flow rate, nominal point m³/h	2869.2	CmH	q _{v,nom}
Nominal external pressure, static	282	Pa	p _{s,nom}
Fan type	Diagonal		Fan _{type}
Category / Installation situation	A		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m³/s	0.8	CmS	q _{v,nom}
Actual electrical input power, nominal point	0.55	kw	P _{e,nom}
Face velocity, nominal point	3.8	mps	V _{nom}
Nominal external pressure, static	282	Pa	p _{s,nom}
supply air fan static efficiency, nominal point	47.5	p	η _{es,SUP}
Enclosure sound level, nominal point	64	db	LWA2
Rating	Product is compliant 2018		



ELKI 6035 E2 10

127736

ruck

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	547	w	P _{ed, max}
Max. operating current (device)	3.17	A	I _{ed, max}
Max. speed	2850	rpm	n _{max}
Max. stat. efficiency	47.8	p	η _{es}
Max. fan efficiency	48.3	p	η _e
Max. flowrate	3510	CmH	Q _{v, max}
Max. stat pressure	740	Pa	p _{sf, max}
Max. medium temperature	70	°C	T _{m, max}
Max. environment temperature	70	°C	T _{amb, max}
Min. environment temperature	-25	°C	T _{amb, min}
Min. voltage	80	v	U _{min}


MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 1~		phase
Control type		stepless-controlled		ctrltype
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TMI		protectmotor
Protection class		IP54		IP _{motor}
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwr _{sup} motor
Capacity capacitor		10	μF	C _{cond}
Voltage capacitor		400	v	VU _{cond}
Number of poles (1)		2.000000		num poles _{w1}
Rated voltage	230		v	U _{rated, f1}
Rated current	1.9		A	I _{rated, f1}
Nominal power	300		w	P _a
Speed	2820		rpm	n _{r1}
Cos Phi	0.990000	0.000000		cos φ
UL-Certification motor		None		UL _{cert}



to the product detail page

CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS




127736 00



ELKI 6035 E2 10

127736

ruck




127736 00



ELKI 6035 E2 10


127736

ruck




ELKI 6035 E2 10

127736



to the product detail page






MECHANICAL ACCESSORIES

VS 6035 | 102808



- Duct connector, flexible
- Standard profile flange P20
- Galvanized steel sheet, plastic band (PVC)
- Temperature resistant up to 70 °C

SDE 6035 L02 | 127751



- Duct silencer
- Sendzimir galvanized sheet steel housing
- Sound absorption by mineral wool with fleece covering on air side
- 20 mm flange profiles

VKK 6035 | 169684



- Automatic shutter
- Plastic, weather resistant
- Temperature resistant up to 70 °C



ELECTRICAL ACCESSORIES

GS 01 | 102787



- Isolator switch
- $U_{max} = 400 \text{ V}$, 50/60 Hz
- Switching capacity 400 V 3~ = 7,5 kW
- $I_{max} = 25 \text{ A}$

TEM 035 | 103502



- 5-step transformer
- 230 V, 50/60 Hz, 3.5 A
- Output voltage: 230-190-170-140-110-80-0 V
- Protection class IP 54

TES 035 02 | 146195



- 5-step transformer
- 230 V, 50/60 Hz, 3.5 A
- Without housing, control cabinet installation
- Protection class IP 20



to the product detail page