

ELKI 7040 D2 10


165382

- Efficiency optimized diagonal fan
- Optimally tuned and CFD-optimized aerodynamics
- Soundproof housing made of galvanized sheet steel
- Removable fan unit
- Efficient IE3 motor, frequency controllable
- Attention! 230 V power supply! 3x400 V forbidden! FU-operation!
See operating instructions!



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

ELKI 7040 D2 10

165382

ruck

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	700x400		WxH _{duct}
Pipe connection size (DN)	-		DN
Rated voltage (entire device)	230	v	U _{rated}
Phases (entire device)	3~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Galvanized steel		mat _{casing}
Impeller material	Plastic		mat _{impeller}
IP-protection class (entire device)	IPX4		IP _{compl}
Weight	43.1	kg	m
Nominal air flow rate, nominal point m³/h	5014.8	CmH	q _{v,nom}
Nominal external pressure, static	582.3	Pa	p _{s,nom}
Fan type	Diagonal		Fan _{type}
Category / Installation situation	A		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m³/s	1.39	CmS	q _{v,nom}
Actual electrical input power, nominal point	1.53	kw	P _{e,nom}
Face velocity, nominal point	8.9	mps	V _{nom}
Nominal external pressure, static	582.3	Pa	p _{s,nom}
supply air fan static efficiency, nominal point	63.7	p	η _{es,SUP}
Highest external air leakage rate	0.05	p	
Enclosure sound level, nominal point	71	db	LWA2
Rating	Product is compliant 2018		

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	1695	w	P _{ed, max}
Max. operating current (device)	5.4	A	I _{ed, max}
Max. speed	3510	rpm	n _{max}
Max. stat. efficiency	50	p	η _{es}
Max. fan efficiency	51.2	p	η _e
Max. flowrate	8410	CmH	q _{v, max}
Max. stat pressure	1110	Pa	p _{sf, max}
Max. medium temperature	40	°C	T _{m, max}
Max. environment temperature	40	°C	T _{amb, max}
Min. environment temperature	-30	°C	T _{amb, min}



to the product detail page

ELKI 7040 D2 10

165382




MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 3~		phase
Control type		frequency-controlled		ctrltype
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TAO		protectmotor
Protection class		IP44		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 3~		pwrsupmotor
Number of poles (1)		2.000000		num polesw1
Connection	Y			wiringw1
Rated voltage	230		v	Urated, f1
Rated current	3.4		A	Irated, f1
Speed	2820		rpm	nr1
Min. temperature	-30		°C	Tmotor, min
Cos Phi	0.870000	0.000000		cos φ
UL-Certification motor		None		ULcert



CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS




165382 00



ELKI 7040 D2 10

165382

ruck




165382 00




ELKI 7040 D2 10

165382



ELKI 7040 D2 10

165382




to the product detail page

ELKI 7040 D2 10

165382

166575




MECHANICAL ACCESSORIES

VS 7040 | 103951



- Duct connector, flexible
- Standard profile flange P20
- Galvanized steel sheet, plastic band (PVC)
- Temperature resistant up to 70 °C

SDE 7040 L02 | 127753



- Duct silencer
- Sendzimir galvanized sheet steel housing
- Sound absorption by mineral wool with fleece covering on air side
- 20 mm flange profiles

VKK 7040 | 169685



- Automatic shutter
- Plastic, weather resistant
- Temperature resistant up to 70 °C



to the product detail page

ELECTRICAL ACCESSORIES

GS 03 | 107633



- Device switch
- $U_{max} = 400 \text{ V}$, $I_{max} = 25 \text{ A}$
- Switching capacity $400 \text{ V } 3\sim = 7,5 \text{ kW}$
- Protection class IP 55

CON P1000 | 115259



- Constant pressure control
- Actual value display possible via optional control unit
- Output 0-10 V DC + FC enable + setpoint reached
- Pressure setting by means of decade switch

MTP 20 | 128146



- Potentiometer 10 k Ω
- Switching contact 1A/250V AC - 2,5A/12V DC
- Max. ambient temperature 50 °C
- VDE

MTP 30 | 143289



- Stepped potentiometer 10 k Ω
- Step 1 + 2 settable 10 % - 100 % Vdc
- Step 3 100 % Vdc
- Supply voltage +10 Vdc

MTP 40 | 147359



- Potentiometer 10 k Ω
- Connection in terminal box
- Max. ambient temperature 50 °C
- PU: 20 pieces

FU 15 56 | 165020



- Frequency converter
- Supply voltage 230 V 1~ 50/60 Hz
- Output voltage 0 - 230 V 3~
- Protection class IP 20, for switch cabinet

FU 15 57 | 165021



- Frequency converter IP66
- Supply voltage 230 V 1~ 50/60 Hz
- Output voltage 0 - 230 V 3~
- Fire mode function (smoke extract fans)



to the product detail page