

KVR 10050 EC 30


131373

- Backward curved centrifugal impeller
- Removable fan unit
- Housing made of galvanized sheet steel
- High efficiency EC motor, steplessly controllable
- Conveyed medium temperature up to 60 °C in continuous operation



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

KVR 10050 EC 30

131373

ruck

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	1000x500		WxH _{duct}
Pipe connection size (DN)	-		DN
Rated voltage (entire device)	400	v	U _{rated}
Phases (entire device)	3~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Galvanized steel		mat _{casing}
Impeller material	Plastic		mat _{impeller}
Weight	65.5	kg	m
Nominal air flow rate, nominal point m³/h	7441.2	CmH	q _{v,nom}
Nominal external pressure, static	691.6	Pa	p _{s,nom}
Fan type	Radial		Fan _{type}
Category / Installation situation	A		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m³/s	2.07	CmS	q _{v,nom}
Actual electrical input power, nominal point	2.08	kw	P _{e,nom}
Face velocity, nominal point	4.1	mps	v _{nom}
Nominal external pressure, static	691.6	Pa	p _{s,nom}
supply air fan static efficiency, nominal point	67.7	p	η _{es,SUP}
Enclosure sound level, nominal point	84	db	LWA2
Rating	Product is compliant 2018		

MAXIMAL DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Max. power consumption (device)	3490	3490	w	P _{ed, max}
Max. operating current (device)	5.31	5.31	A	I _{ed, max}
Max. speed	1790	1790	rpm	n _{max}
Max. stat. efficiency	64.3	64.3	p	η _{es}
Max. fan efficiency	65.3	65.3	p	η _e
Max. flowrate	14960	14960	CmH	q _{v, max}
Max. stat pressure	1380	1380	Pa	p _{sf, max}
Max. medium temperature	60	60	°C	T _{m, max}
Max. environment temperature	60	60	°C	T _{amb, max}
Min. environment temperature	-30	-30	°C	T _{amb, min}



to the product detail page

KVR 10050 EC 30

131373

ruck

MOTOR DATA


Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		EC		phase
Control type		stepless-controlled		ctrlype
Installation type		ORM (Out)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TEC		protectmotor
Protection class		IP55		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 3~		pwrsupmotor
Rated voltage	400	400	v	U _{rated, f1}
Rated current	5.4	5.4	A	I _{rated, f1}
Nominal power	3500	3500	w	P _a
Speed	1750	1750	rpm	n _{f1}
Min. temperature	-40	-40	°C	T _{motor, min}
UL-Certification motor		UL recognized		ULcert

SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Fire resistance class	None		Fclass




CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



KVR 10050 EC 30

131373




131373 01



to the product detail page

KVR 10050 EC 30


131373



to the product detail page

KVR 10050 EC 30

131373




to the product detail page

KVR 10050 EC 30

131373

169852



MECHANICAL ACCESSORIES

VKK 10050 | 169687



- Automatic shutter
- Plastic, weather resistant
- Temperature resistant up to 70 °C

VS 10050 | 172499



- Duct connector, flexible
- Standard profile flange P30
- Galvanized steel sheet, plastic band (PVC)
- Temperature resistant up to 70 °C



to the product detail page

ELECTRICAL ACCESSORIES

GS 03 | 107633



- Device switch
- $U_{max} = 400\text{ V}$, $I_{max} = 25\text{ A}$
- Switching capacity $400\text{ V } 3\sim = 7,5\text{ kW}$
- Protection class IP 55

CON P1000 | 115259



- Constant pressure control
- Actual value display possible via optional control unit
- Output 0-10 V DC + FC enable + setpoint reached
- Pressure setting by means of decade switch

MTP 20 | 128146



- Potentiometer 10 k Ω
- Switching contact 1A/250V AC - 2,5A/12V DC
- Max. ambient temperature 50 °C
- VDE

MTP 30 | 143289



- Stepped potentiometer 10 k Ω
- Step 1 + 2 settable 10 % - 100 % Vdc
- Step 3 100 % Vdc
- Supply voltage +10 Vdc

MTP 40 | 147359



- Potentiometer 10 k Ω
- Connection in terminal box
- Max. ambient temperature 50 °C
- PU: 20 pieces

MTP 50 | 168752



- Potentiometer with multifunction output
- 230 VAC $\pm 10\%$ / 50-60 Hz
- Selectable output: 1-10 VDC / 2-20 mA / 10-100 % PWM
- Min. and max. output value adjustable



to the product detail page