

KVRI 4020 EC 32


159291

- Backward curved centrifugal impeller
- Swing out fan unit
- Galvanized sheet steel housing, double-walled, 25 mm mineral wool
- High efficiency EC motor, steplessly controllable
- Conveyed medium temperature up to 60 °C in continuous operation



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	400x200		WxH _{duct}
Pipe connection size (DN)	-		DN
Rated voltage (entire device)	230	v	U _{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Galvanized steel		mat _{casing}
Impeller material	Plastic		mat _{impeller}
Weight	14.14	kg	m
Nominal air flow rate, nominal point m³/h	522	CmH	q _{v,nom}
Nominal external pressure, static	209.8	Pa	p _{s,nom}
Fan type	Radial		Fan _{type}
Category / Installation situation	B		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m³/s	0.15	CmS	q _{v,nom}
Actual electrical input power, nominal point	0.06	kw	P _{e,nom}
Face velocity, nominal point	1.8	mps	v _{nom}
Nominal external pressure, static	209.8	Pa	p _{s,nom}
supply air fan static efficiency, nominal point	55.3	p	η _{es,SUP}
Highest external air leakage rate	3.07	p	
Enclosure sound level, nominal point	69	db	LWA2
Rating	Product is compliant 2018		

MAXIMAL DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Max. power consumption (device)	172	172	w	P _{ed, max}
Max. operating current (device)	1.52	1.52	A	I _{ed, max}
Max. speed	2760	2760	rpm	n _{max}
Max. stat. efficiency	48.4	48.4	p	η _{es}
Max. fan efficiency	48.9	48.9	p	η _e
Max. flowrate	1330	1330	CmH	q _{v, max}
Max. stat pressure	650	650	Pa	p _{sf, max}
Max. medium temperature	50	50	°C	T _{m, max}
Max. environment temperature	50	50	°C	T _{amb, max}
Min. environment temperature	-30	-30	°C	T _{amb, min}



KVRI 4020 EC 32

159291



MOTOR DATA


Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		EC		phase
Control type		stepless-controlled		ctrltype
Installation type		ORM (Out)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TEC		protectmotor
Protection class		IP54		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwrsupmotor
Rated voltage	230	230	v	Urated, f1
Rated current	1.2	1.2	A	Irated, f1
Speed	2600	2600	rpm	nr1
Efficiency	46.9	46.9	p	ηm, f1
Min. temperature	-30	-30	°C	Tmotor, min
Cos Phi	0.600000	0.600000		cos φ
UL-Certification motor		None		ULcert

SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Fire resistance class	None		Fclass



CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



159291 01




to the product detail page

KVRI 4020 EC 32


159291

ruck



KVRI 4020 EC 32

159291




to the product detail page



KVRI 4020 EC 32


159291

ruck



159291 01





MECHANICAL ACCESSORIES

VS 4020 | 102802



- Duct connector, flexible
- Standard profile flange P20
- Galvanized steel sheet, plastic band (PVC)
- Temperature resistant up to 70 °C

VKK 4020 | 169680



- Automatic shutter
- Plastic, weather resistant
- Temperature resistant up to 70 °C



to the product detail page

ELECTRICAL ACCESSORIES

GS 03 | 107633



- Device switch
- $U_{max} = 400\text{ V}$, $I_{max} = 25\text{ A}$
- Switching capacity $400\text{ V } 3\sim = 7,5\text{ kW}$
- Protection class IP 55

CON P1000 | 115259



- Constant pressure control
- Actual value display possible via optional control unit
- Output 0-10 V DC + FC enable + setpoint reached
- Pressure setting by means of decade switch

MTP 20 | 128146



- Potentiometer 10 k Ω
- Switching contact 1A/250V AC - 2,5A/12V DC
- Max. ambient temperature 50 °C
- VDE

MTP 30 | 143289



- Stepped potentiometer 10 k Ω
- Step 1 + 2 settable 10 % - 100 % Vdc
- Step 3 100 % Vdc
- Supply voltage +10 Vdc

MTP 40 | 147359



- Potentiometer 10 k Ω
- Connection in terminal box
- Max. ambient temperature 50 °C
- PU: 20 pieces

MTP 50 | 168752



- Potentiometer with multifunction output
- 230 VAC $\pm 10\%$ / 50-60 Hz
- Selectable output: 1-10 VDC / 2-20 mA / 10-100 % PWM
- Min. and max. output value adjustable

