

KVRI 6035 EC 30


131437

- Backward curved centrifugal impeller
- Swing out fan unit
- Galvanized sheet steel housing, double-walled, 25 mm mineral wool
- High efficiency EC motor, steplessly controllable
- Conveyed medium temperature up to 60 °C in continuous operation



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

KVRI 6035 EC 30

131437

ruck

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	600x350		WxH _{duct}
Pipe connection size (DN)	-		DN
Rated voltage (entire device)	230	v	U _{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Galvanized steel		mat _{casing}
Impeller material	Plastic		mat _{impeller}
IP-protection class (entire device)	IPX4		IP _{compl}
IP-Protection class (terminal box)	IP44		IP _{ebox}
Weight	34.4	kg	m
Nominal air flow rate, nominal point m³/h	1155.6	CmH	q _{v,nom}
Nominal external pressure, static	161.3	Pa	p _{s,nom}
Fan type	Radial		Fa _n type
Category / Installation situation	A		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m³/s	0.32	CmS	q _{v,nom}
Actual electrical input power, nominal point	0.09	kw	P _{e,nom}
Face velocity, nominal point	1.5	mps	V _{nom}
Nominal external pressure, static	161.3	Pa	p _{s,nom}
supply air fan static efficiency, nominal point	63.4	p	η _{es,SUP}
Enclosure sound level, nominal point	60	db	LWA2
Rating	Product is compliant 2018		



MAXIMAL DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Max. power consumption (device)	164	164	w	P _{ed, max}
Max. operating current (device)	1.37	1.37	A	I _{ed, max}
Max. speed	1540	1540	rpm	n _{max}
Max. stat. efficiency	53.9	53.9	p	η _{es}
Max. fan efficiency	54.7	54.7	p	η _e
Max. flowrate	2845	2845	CmH	Q _{v, max}
Max. stat pressure	465	465	Pa	p _{sf, max}
Max. medium temperature	60	60	°C	T _{m, max}
Max. environment temperature	60	60	°C	T _{amb, max}
Min. environment temperature	-25	-25	°C	T _{amb, min}

MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		EC		phase
Control type		stepless-controlled		ctrltype
Installation type		ORM (Out)		install
Rotation direction		right		rotation
Isolation class		ISO B		ISOclass
Motor-protection		TEC		protectmotor
Protection class		IP54		IP _{motor}
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwr _{sup} motor
Rated voltage	230	230	v	U _{rated, f1}
Rated current	1.4	1.4	A	I _{rated, f1}
Nominal power	168	168	w	P _a
Speed	1250	1250	rpm	n _{f1}
Efficiency	65.5	65.5	p	η _{m, f1}
Min. temperature	-25	-25	°C	T _{motor, min}
UL-Certification motor		UL recognized		ULcert


SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Fire resistance class	None		Fclass



to the product detail page

CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS




131437 00



KVRI 6035 EC 30

131437

ruck




131437 00



KVRI 6035 EC 30

131437


ruck



KVRI 6035 EC 30


131437

ruck



KVRI 6035 EC 30

131437



MECHANICAL ACCESSORIES

VS 6035 | 102808



- Duct connector, flexible
- Standard profile flange P20
- Galvanized steel sheet, plastic band (PVC)
- Temperature resistant up to 70 °C

VKK 6035 | 169684



- Automatic shutter
- Plastic, weather resistant
- Temperature resistant up to 70 °C



to the product detail page

ELECTRICAL ACCESSORIES

GS 03 | 107633



- Device switch
- $U_{max} = 400\text{ V}$, $I_{max} = 25\text{ A}$
- Switching capacity $400\text{ V } 3\sim = 7,5\text{ kW}$
- Protection class IP 55

CON P1000 | 115259



- Constant pressure control
- Actual value display possible via optional control unit
- Output 0-10 V DC + FC enable + setpoint reached
- Pressure setting by means of decade switch

MTP 20 | 128146



- Potentiometer 10 k Ω
- Switching contact 1A/250V AC - 2,5A/12V DC
- Max. ambient temperature 50 °C
- VDE

MTP 30 | 143289



- Stepped potentiometer 10 k Ω
- Step 1 + 2 settable 10 % - 100 % Vdc
- Step 3 100 % Vdc
- Supply voltage +10 Vdc

MTP 40 | 147359



- Potentiometer 10 k Ω
- Connection in terminal box
- Max. ambient temperature 50 °C
- PU: 20 pieces

MTP 50 | 168752



- Potentiometer with multifunction output
- 230 VAC $\pm 10\%$ / 50-60 Hz
- Selectable output: 1-10 VDC / 2-20 mA / 10-100 % PWM
- Min. and max. output value adjustable



to the product detail page