

RS 250L


130363

- Compact centrifugal fan
- Backward curved impeller
- Sheet steel housing, RAL 7035, powder coated
- Robust single phase AC motor, steplessly controllable
- Conveyed medium temperature up to 50 °C in continuous operation
- Integrated thermal switch



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	none		
Duct size	-		WxH _{duct}
Pipe connection size (DN)	DN250		DN
Rated voltage (entire device)	230	v	U _{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Steel		mat _{casing}
Impeller material	Galvanized steel		mat _{impeller}
IP-protection class (casing)	IPX4		IP _{casing}
IP-protection class (entire device)	IPX4		IP _{compl}
IP-Protection class (terminal box)	IP44		IP _{ebox}
Weight	5.05	kg	m
Nominal air flow rate, nominal point m³/h	698.4	CmH	q _{v,nom}
Nominal external pressure, static	332.3	Pa	p _{s,nom}
Fan type	Radial		Fan _{type}
Category / Installation situation	A		cat

ERP DATA (LOT 6)

Name	Value	Unit	Formula symbol
Nominal air flow rate, nominal point m³/s	0.19	CmS	q _{v,nom}
Actual electrical input power, nominal point	0.19	kw	P _{e,nom}
Face velocity, nominal point	4	mps	V _{nom}
Nominal external pressure, static	332.3	Pa	p _{s,nom}
supply air fan static efficiency, nominal point	39.8	p	η _{es,SUP}
Highest external air leakage rate	0.35	p	
Enclosure sound level, nominal point	64	db	LWA2
Rating	Product is not compliant		



to the product detail page

MAXIMAL DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Max. power consumption (device)	192	256	W	P _{ed, max}
Max. operating current (device)	0.91	1.19	A	I _{ed, max}
Max. speed	2800	3260	rpm	n _{max}
Max. stat. efficiency	31.7	27.7	p	η _{es}
Max. fan efficiency	32.6	28.3	p	η _e
Max. flowrate	1270	1400	CmH	Q _{v, max}
Max. stat pressure	570	770	Pa	p _{sf, max}
Max. medium temperature	50	60	°C	T _{m, max}
Max. environment temperature	50	60	°C	T _{amb, max}
Min. environment temperature	-25	-25	°C	T _{amb, min}
Min. voltage	80	80	V	U _{min}
Stall current	1.75		A	I _{LRA}

MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 1~		phase
Control type		stepless-controlled		ctrltype
Installation type		ORM (Out)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TAI		protect _{motor}
Protection class		IP33		IP _{motor}
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwr _{sup} _{motor}
Capacity capacitor		5	μF	C _{cond}
Voltage capacitor		400	V	V _{Ucond}
Number of poles (1)		2.000000		num poles _{w1}
Rated voltage	230	230	V	U _{rated, f1}
Rated current	0.88	1.14	A	I _{rated, f1}
Speed	2525	2730	rpm	n _{f1}
Starting current	1.75	1.75	A	I _{start, f1}
Efficiency	40.1	36.1	p	η _{m, f1}
Min. temperature	-30		°C	T _{motor, min}
Cos Phi	0.980000	0.000000		cos φ
UL-Certification motor		None		ULcert



to the product detail page

RS 250L

130363




SMOKE EXTRACT DATA

Name	Value	Unit	Formula symbol
Fire resistance class	None		Fclass




CIRCUIT DIAGRAMS / DIMENSIONAL DRAWINGS



RS 250L

130363




130363 00



to the product detail page

RS 250L


130363




to the product detail page

RS 250L

130363



to the product detail page



MECHANICAL ACCESSORIES

VM 250 | 102651



- Fast clamps for sound decoupling and sealing
- Galvanized steel sheet, 5 mm Neopren gasket
- 1 Pack = 2 pieces

RSK 250 | 102686




- Back draught shutter for tube fitting
- Galvanized steel sheet housing
- Aluminum flaps

MRS 2 | 110095




- Mounting bracket
- Galvanized steel sheet
- Includes: Mounting bracket and 2 Phillips screws (6 x 45 mm), 2 dowels (8 x 40 mm)

FV 250 | 112833



- Air filter box with mat filter ISO Coarse 45 % (G3)
- Toggle-type fastener

FT 250 | 112845



- Air filter box for pocket filter
- Toggle-type fastener
- Galvanized steel sheet housing
- Without filter

FTW 250 | 112854



- Air filter box with pocket filter M5
- Integrated warm water heating coil
- Galvanized steel sheet housing
- Toggle-type fastener

RSK 250D | 113488



- Back draught shutter for tube fitting
- Galvanized steel sheet housing
- Aluminum flaps
- Integrated gasket

KWR 250 01 | 124065




- Cold water cooler, uninsulated
- Version right
- Connection ND 250
- Galvanized steel sheet with condensate tray

KWR 250 02 | 124066



- Cold water cooler, uninsulated
- Version left
- Connection ND 250
- Galvanized steel sheet with condensate tray

SG 250 01 | 169588



- Protection grille for tube connection
- Galvanized wire

SDS 250 | 169607



- Rigid tube silencer
- Galvanized steel sheet
- Sound insulation packing 50 mm (mineral wool)

SDF 250 | 169644



- Flexible tube silencer
- Galvanized steel sheet
- Sound insulation packing 50 mm



ELECTRICAL ACCESSORIES

GS 01 | 102787



- Isolator switch
- $U_{max} = 400\text{ V}$, 50/60 Hz
- Switching capacity 400 V 3~ = 7,5 kW
- $I_{max} = 25\text{ A}$

MTY 1 | 103428



- Electronic controller
- Stepless
- 230 V ~, 50 Hz
- Max. ambient temperature 35 °C
- $I_{max} = 1\text{ A}$
- Surface and flush mounting

ETY 15 | 115891



- Electronic controller
- Stepless speed control
- 230 V ~, 50 Hz, 2,5 A
- Max. ambient temperature 35 °C

TEE 015 | 115893



- 5-step transformer
- 230 V ~, 50/60 Hz

TES 0145 | 169581



- Step transformer
- 230 V ~, 50/60 Hz

